

Overviews

EMA-XX-SDI is our latest CBVS RCA input Encoder Modulator . It support 4 channel , 8 channel , 12 channel , 16 channel , 20 channel , 24 channel AV input , 1*10/100/1000M IP in/out ports ; 4 MPTS input and 512 SPTS output , 128 IP input .It has the characteristics of high integration, high performance and low cost.

Feature

- Support 4 channels/8 channels/12 channels/16 channels/20 channels/24 channels AV input
- Support 1 channel Gigabit IP input/output, UDP/RTP protocol (multicast)
- Support 2 ASI inputs
- Support 2 ASI output
- Support LCD and button functions
- Support network management (Web) support online upgrade

Front



1-LED DISPLAY	2- INDICATOR LIGHT
3-BUTTON	4-ASI INPUT
5-ASI OUTPUT	6-NMS&DATA PORTS

Back



1-RCA CVBS INPUT	2- AC110/220V POWER SUPPLY
------------------	----------------------------

Specification

Item	Parameter		
Input	CVBS RCA (4/8/12/16/20/24)		
	2*ASI input		
	128*IP input		
Output	2*ASI output		
	4*MPTS, 512*SPTS IP output		
Video encoding	Encoding format	SD MPEG-2	
	input interface	CVBS RCA	
	Resolution	Input : 720x576i/720x480i (PAL/NTSC)	
		Output : 720x576 / 720x480 (PAL/NTSC)	
		544x576 / 544x480 (PAL/NTSC)	
		480x576 / 480x480 (PAL/NTSC)	
		352x576 / 352x480 (PAL/NTSC)	
	352x288 / 352x240 (PAL/NTSC)		
176x144 / 176x112 (PAL/NTSC)			
Bit Rate	1Mbps~19Mbps (Per channel)		
Bit rate mode	CBR		
Encoding format	MPEG1 Layer2		
Modulator	DVB-T,DVB-C,ISDB-T.. Modulation		
General	Sampling Rate	48KHz	
	Bit	64,128,192,256,320,384kbps	
	temperature range	0~45°C(work) ; -20~80°C(storage)	
	Power requirement	AC110~240V , 50/60Hz	
	Power consumption	<90W	



We produce a wide selection of network equipment under HONDAO brand . Gather thousands of products ,which are supplier to customs of different filed and different requirement . QC team test all goods before shipment . We screen the Chinese supplier in a search of the most efficient product solutions available to satisfy your individual needs .